

# WAC LIGHTING


Responsible Lighting®

InvisiLED® Pro / Pro2




*High Performance*

InvisiLED® Classic 24V




*White + 4 colors*

InvisiLED® Palette  
Daylight to Sunset



*Color changing*

InvisiLED® Outdoor





*IP68, Wet location*





Year  
warranty







### The Pro2 Advantage: Superior Brightness

InvisiLED Pro2 features up to 330 lumens per foot of illumination. Two lengths of Pro2 is the lumen equivalent of a T5 fluorescent lamp but may be concealed within smaller cavities and offer greater application efficiency with 120° directional illumination. This enables the light to be visible even amidst brightly lit spaces such as the shopping mall depicted above.

Featured Product: **LED-TX2435-5-WT** as cove lighting





# InvisiLED® Pro2



**Power:** 4W / ft  
**Lumens:** Up to 330 lm / ft  
**CRI:** 85  
**Rated Life:** 50,000 hours

- Designed for super bright cove or task lighting
- 5 year warranty
- UL listed for damp location

- Maximum run length of 25 feet
- May be field cut every 6 inches at the end of a run
- Dimmable with an Electronic Low Voltage (ELV) dimmer



## Tape Selections

System	Color Temp	Length	Qty	Finish
<b>LED-TX24</b>	<b>27</b> 2700K	<b>6IN</b> 6 inches	1	<b>WT</b> White
	<b>30</b> 3000K	<b>1</b> 1 foot	1	
	<b>35</b> 3500K	<b>5</b> 5 feet	1	
	<b>45</b> 4500K	<b>1-40</b> 1 foot	40	




Example: **LED-TX2435-6IN-WT**

## 5 LED "L" Connector

System	Color Temp	Finish
<b>LED-TX24</b>	<b>27</b> 2700K	<b>5L-WT</b> White
	<b>30</b> 3000K	
	<b>35</b> 3500K	
	<b>45</b> 4500K	

Example: **LED-TX2435-5L-WT**

## Class 2 Power Supply for Pro 2 (Required)

Type	Model	Power	Dim	Input	Output
Remote	 <b>EN-2460-RB2-T</b> <b>EN-24100-RB2-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC
Plug-in	 <b>EN-2460-P-AR-T</b> <b>EN-24100-P-AR-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC
Remote 277V	 <b>EN-24100-277-R</b>	96W	No	277V AC	24V DC





*Includes a 6 foot lead wire*

*Includes a 6 foot lead wire*

*Order with LED-TC-B-2 or LED-T-EXT-144*

## Accessories

Rigid Aluminum Channel	 <b>LED-T-CH</b>	5 ft	Includes mounting hardware and diffuser lens
Lead Wire	 <b>LED-TC-P-2</b> <b>LED-TC-P-12</b>	2 ft 12 ft	Alternative lengths for power supplies
Extension Cable	 <b>LED-TC-EXT-144</b>	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Wiring Box With Switch	 <b>TB-S</b>	L: 6 1/4 in W: 1 5/8 in H: 1 1/4 in	Use when spanning a large gap in a system layout without leaving exposed wiring
Low Voltage Wiring Box	 <b>LED-T-B</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly house up to two wires
Low Voltage Wiring Box With Feed	 <b>LED-TC-B-2</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly house up to two wires With 2" female feed

Joiner Cable	 <b>LED-TC-IC2</b> 2 in <b>LED-TC-IC6</b> 6 in <b>LED-TC-IC12</b> 12 in <b>LED-TC-IC36</b> 36 in <b>LED-TC-IC72</b> 72 in	Use between tape sections
4-Way "X" Connector	 <b>LED-TC-X</b>	
3-Way "Y" Connector	 <b>LED-TC-Y</b>	
"L" Connector	 <b>LED-TC-L</b>	
End cap	 <b>LED-TC-EC</b>	1 cut end cap 1 male end cap
Mounting Clips	 <b>LED-T-CL</b>	10 Qty
Retrofit Channel	 <b>LED-T-RC</b>	36 in





### The Pro Experience: Customize Functionality

InvisiLED Pro provides the most custom options from a bright task and cove lighting solution providing over 200 lumens per foot. Four color temperatures accentuate the color scheme of the space, ranging from 2700K to bring out the warmth of wood stains to 4500k for clean and bright white spaces. Customize illuminated run lengths within 2 inches of accuracy to perfectly match custom cabinets with consistent 1 inch on-center spacing of diodes even through junctions of sections.

Featured Product: **LED-T24W-5-WT** as cove and undercabinet lighting





# InvisiLED® Pro



**Power:** 3W/ft  
**Lumens:** Up to 215 lm/ft  
**CRI:** 85  
**Rated Life:** 50,000 hours

- Designed for bright cove or task lighting
- 5 year warranty
- UL listed for damp location
- Maximum run length of 33 feet
- May be field cut every 2 inches at the end of a run
- Dimmable with an Electronic Low Voltage (ELV) dimmer



## Tape Selections

System	Color Temp	Length	Qty	Finish
LED-T24	W 2700K	2IN 2 inches	1	WT White
	P 3000K	2IN-10 2 inches	10	
	35 3500K	1 1 foot	1	
	C 4500K	5 5 feet	1	
		1-40 1 foot	40	




Example: **LED-T24W-1-40-WT**

### 3 LED "L" Connector

System	Color Temp	Finish
LED-T24	W 2700K	3L-WT White
	P 3000K	
	35 3500K	
	C 4500K	








Example: **LED-T24W-3L-WT**

## Class 2 Power Supply for Pro (Required)

Type		Model	Power	Dim	Input	Output	
Remote		<b>EN-2460-RB2-T</b> <b>EN-24100-RB2-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC	Includes a 6 foot lead wire
Plug-in		<b>EN-2460-P-AR-T</b> <b>EN-24100-P-AR-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC	Includes a 6 foot lead wire
Remote 277V		<b>EN-24100-277-R</b>	96W	No	277V AC	24V DC	Order with LED-TC-B-2 or LED-T-EXT-144

## Accessories

Rigid Aluminum Channel		<b>LED-T-CH</b>	5 ft	Includes mounting hardware and diffuser lens
Lead Wire		<b>LED-TC-P-2</b> <b>LED-TC-P-12</b>	2 ft 12 ft	Alternative lengths for power supplies
Extension Cable		<b>LED-TC-EXT-144</b>	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Wiring Box With Switch		<b>TB-S</b>	L: 6¼ in W: 1½ in H: 1¼ in	Use when spanning a large gap in a system layout without leaving exposed wiring
Low Voltage Wiring Box		<b>LED-T-B</b>	L: 1½ in W: ¾ in H: ⅞ in	Neatly house up to two wires
Low Voltage Wiring Box With Feed		<b>LED-TC-B-2</b>	L: 1½ in W: ¾ in H: ⅞ in	Neatly house up to two wires With 2" female feed

Joiner Cable		<b>LED-TC-IC2</b> 2 in <b>LED-TC-IC6</b> 6 in <b>LED-TC-IC12</b> 12 in <b>LED-TC-IC36</b> 36 in <b>LED-TC-IC72</b> 72 in	Use between tape sections
4-Way "X" Connector		<b>LED-TC-X</b>	
3-Way "Y" Connector		<b>LED-TC-Y</b>	
"L" Connector		<b>LED-TC-L</b>	
End cap		<b>LED-TC-EC</b>	1 cut end cap 1 male end cap
Mounting Clips		<b>LED-T-CL</b>	10 Qty
Retrofit Channel		<b>LED-T-RC</b>	36 in



### The Classic Approach: Style Accents

InvisiLED Classic 24 series offers 4 rich colors and White light at over 100 lumens per foot. Highlight your space with unique accent and display lighting applications in cabinets, around moldings, or under counters and steps. In this unique diminutive size, InvisiLED Classic allows you to light spaces never lit before to achieve the ultimate layered lighting effect.

Featured Product: **LED-T24-5-AM** with **LED-T-CH**







**Power:** 2W / ft  
**Lumens:** Up to 115 lm / ft  
**CRI:** 85  
**Rated Life:** 50,000 hours

- Designed for accent lighting
- 5 year warranty
- UL listed for damp location

- Maximum run length 40 feet
- May be field cut every 2 inches at the end of a run
- Dimmable with an Electronic Low Voltage (ELV) dimmer



## Tape Selections

System	Length	Qty	Color
<b>LED-T24</b>	<b>2IN</b> 2 inches	1	<b>AM</b> Amber 590-595nm
	<b>1</b> 1 foot	1	<b>BL</b> Blue 465-470nm
	<b>5</b> 5 feet	1	<b>GR</b> Green 515-520nm
			<b>RD</b> Red 625-630nm
<b>LED-T2430</b>	<b>2IN</b> 2 inches	1	<b>WT</b> White 3000K
	<b>2IN-10</b> 2 inches	10	
	<b>1</b> 1 foot	1	
	<b>1-40</b> 1 foot	40	
	<b>5</b> 5 feet	5	

## 3 LED "L" Connector

**LED-T2430-3L-WT** White 3000K

Example: **LED-T2430-1-40-WT**

## Class 2 Power Supply for Classic 24V (Required)














Type	Model	Power	Dim	Input	Output
Remote	<b>EN-2460-RB2-T</b> <b>EN-24100-RB2-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC
Plug-in	<b>EN-2460-P-AR-T</b> <b>EN-24100-P-AR-T</b>	60W 96W	Yes	120V AC	24V AC 24V AC
Remote 277V	<b>EN-24100-277-R</b>	96W	No	277V AC	24V DC

*Includes a 6 foot lead wire*

*Includes a 6 foot lead wire*

*Order with LED-TC-B-2 or LED-T-EXT-144*

## Accessories

Rigid Aluminum Channel		<b>LED-T-CH</b>	5 ft	Includes mounting hardware and diffuser lens
Lead Wire		<b>LED-TC-P-2</b> <b>LED-TC-P-12</b>	2 ft 12 ft	Alternative lengths for power supplies
Extension Cable		<b>LED-TC-EXT-144</b>	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Wiring Box With Switch		<b>TB-S</b>	L: 6 1/4 in W: 1 5/8 in H: 1 1/4 in	Use when spanning a large gap in a system layout without leaving exposed wiring
Low Voltage Wiring Box		<b>LED-T-B</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly house up to two wires
Low Voltage Wiring Box With Feed		<b>LED-TC-B-2</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly house up to two wires With 2" female feed
Joiner Cable		<b>LED-TC-IC2</b> 2 in <b>LED-TC-IC6</b> 6 in <b>LED-TC-IC12</b> 12 in <b>LED-TC-IC36</b> 36 in <b>LED-TC-IC72</b> 72 in		Use between tape sections
4-Way "X" Connector		<b>LED-TC-X</b>		
3-Way "Y" Connector		<b>LED-TC-Y</b>		
"L" Connector		<b>LED-TC-L</b>		
End cap		<b>LED-TC-EC</b>		1 cut end cap 1 male end cap
Mounting Clips		<b>LED-T-CL</b>	10 Qty	
Retrofit Channel		<b>LED-T-RC</b>	36 in	

470nm


630nm

600nm


520nm

Featured Product: **LED-TC-5-RGB**

Wireless controller (accessory for wired controller)  
**LED-TO24-WS**



Wired controller  
**LED-TC-CTR-MSD**



## InvisiLED® Daylight to Sunset


## InvisiLED® Palette

5100K

595nm

- Power:** 1.5W / ft
- Rated Life:** 50,000 hours
- Color changing from cool white to amber
  - DMX integration possible
  - Maximum run length of 40 feet
  - May be field cut every 6 inches at the end of a run
  - 5 year warranty
  - UL listed for damp location


- Power:** 1.5W / ft
- Rated Life:** 50,000 hours
- Variable colors with 3500K White
  - DMX integration possible
  - Maximum run length of 40 feet
  - May be field cut every 6 inches at the end of a run
  - 5 year warranty
  - UL listed for damp location



### Tape Selections

System	Length	Qty	
<b>LED-TC</b>	<b>1</b>	1 foot	1
	<b>5</b>	5 feet	1
	<b>1-40</b>	1 foot	40
			<b>WA</b>

Example: **LED-TC-5-WA**





### Tape Selections


System	Length	Qty	
<b>LED-TC</b>	<b>1</b>	1 foot	1
	<b>5</b>	5 feet	1
	<b>1-40</b>	1 foot	40
			<b>RGB</b>

Example: **LED-TC-1-40-RGB**



### Class 2 Power Supply for Daylight to Sunset and Palette (Required)





Type	Model	Power	Dim	Input	Output
Remote	 <b>EN-2460D-C</b>	60W	Yes	120V AC	24V DC 60W
Plug-in	 <b>EN-2460D-C-P</b>	60W	Yes	120V AC	24V DC 60W

### Controller for Daylight to Sunset and Palette (Required)

Wired controller	 <b>LED-TC-CTR-MSD</b>	4 function wired controller	Allows brightness control, preset color selection, or plays a rotation of color transitions with variable speed control
------------------	---	-----------------------------	---

### Accessories

Wireless Controller	 <b>LED-TO24-WS</b>	4 function wireless controller (Requires wired controller)
Rigid Aluminum Channel	 <b>LED-T-CH</b>	5 ft Includes mounting hardware and diffuser lens
Signal Wire	 <b>LED-TC24-SW60</b> <b>LED-TC24-SW120</b>	60 in 120 in Links master and slave controllers
Joiner Cable	 <b>LED-TC-IC2</b> <b>LED-TC-IC6</b> <b>LED-TC-IC12</b> <b>LED-TC-IC36</b> <b>LED-TC-IC72</b>	2 in 6 in 12 in 36 in 72 in Use between tape sections

4-Way "X" Connector		LED-TC-X	
3-Way "Y" Connector		LED-TC-Y	
"L" Connector		LED-TC-L	
End cap		LED-TC-EC	1 cut end cap 1 male end cap
Mounting Clips		LED-T-CL	10 Qty
Retrofit Channel		LED-T-RC	36 in




The highest IP rating: IP68

Submersible up to 5 feet  
Dust tight




# InvisiLED® Pro Outdoor



- Power:** 2W / ft (Color)  
3.5W / ft (White)
- Lumens:** Up to 220 lm / ft
- Rated Life:** 50,000 hours
- IP-68 Rated, UL listed for wet location
  - Maximum run length of 40 ft (color), 28 ft (White)
  - May be field cut at the end of a run
  - 5 year warranty

Featured Product: **LED-T2435-5-WT**

Double insulated silicon encasement and distinct electrical and mechanical junctions make for a superior watertight custom system




## Tape Selections






System	Length		Color		Power consumption	
<b>LED-TO24</b>	<b>1</b>	1 foot	<b>AM</b>	Amber	590-595nm	2W / ft
	<b>5</b>	5 feet	<b>BL</b>	Blue	465-470nm	
	<b>10</b>	10 feet	<b>GR</b>	Green	515-520nm	
			<b>RD</b>	Red	625-630nm	
<b>LED-TO2435</b>	<b>1</b>	1 foot	<b>WT</b>	White	3500K	3.5W / ft
	<b>5</b>	5 feet				
	<b>10</b>	10 feet				




Example: **LED-TO2435-10-WT**

## Class 2 Power Supply for Pro Outdoor (Required)


Type	Model	Power	Input	Output	
Remote 	<b>EN-O24100-RB2-T</b>	96W	120V - 277V AC	24V DC	Includes a 6 foot lead wire

## Accessories

Clear Channel 	<b>LED-TO24-CH1</b> 1 foot <b>LED-TO24-CH5</b> 5 feet
End cap 	<b>LED-TO24-EC</b>
Mounting Clip 1 	<b>LED-TO24-C1</b> Secures on both edges (10 Qty)
Mounting Clip 2 	<b>LED-TO24-C2</b> Secures on one edge (10 Qty)
Mounting Clip 3 	<b>LED-TO24-C3</b> Spring clip secures beneath tape (10 Qty)

Joiner Cable		<b>LED-TO24-IC6</b> 6 in <b>LED-TO24-IC12</b> 12 in <b>LED-TO24-IC72</b> 72 in <b>LED-TO24-IC120</b> 120 in	Use between tape sections
4 Way "X" Connector		<b>LED-TO24-X</b>	
3-Way "Y" Connector		<b>LED-TO24-Y</b>	






### The Chameleon Effect

InvisiLED Palette Outdoor offers all the benefits of our Palette and Outdoor Pro series combined into one system designed to allow you to change the ambiance and color scheme of your exterior space at the touch of a button. Versatile enough to suit residential needs for home accent illumination with holiday flair as well as large commercial venues for various event functions that require a DMX link to professional control systems.

Featured Product: **LED-TCO-5-RGB** with **LED-TO24-CH5**




# InvisiLED® Palette Outdoor




**Power:** 1.5W / ft  
**Dimming:** Yes  
**Rated Life:** 50,000 hours

- IP-68 Rated, UL listed for wet location
- Variable colors with 3500K White
- DMX integration possible
- Maximum run length of 40 feet
- May be field cut every 2 inches at the end of a run
- 5 year warranty



Double insulated silicon encasement and distinct electrical and mechanical junctions make for a superior watertight custom system



## Tape Selection

System	Length	Type
<b>LED-TCO</b>	<b>1</b>	1 foot
	<b>5</b>	5 feet
	<b>10</b>	10 feet
		<b>RGB</b>

Example: **LED-TCO-5-RGB**

## Controller for Palette Outdoor (Both Required)

Master Controller		<b>LED-TO24-CM</b>	4 function wired controller
Wireless Controller		<b>LED-TO24-WS</b>	4 function wireless controller

## Class 2 Power Supply for Palette Outdoor (Required)

Type	Model	Power	Input	Output
Remote	<b>EN-O24100-RB2-T</b>	96W	120V - 277V AC	24V DC

Includes a 6 foot lead wire

## Accessories

Slave Controller		<b>LED-TO24-CS</b>	Connects to Master Controller, adding 40 ft run
Signal Wire		<b>LED-TO24-SW60</b>	Master to Slave, 60 in
DMX Signal Wire		<b>LED-TO24-MW60</b>	DMX to Master, 60 in
End cap		<b>LED-TO24-EC</b>	DMX to Master, 120 in
Clear Channel		<b>LED-TO24-CH1</b>	1 foot
		<b>LED-TO24-CH5</b>	5 feet
Mounting Clip 1		<b>LED-TO24-C1</b>	Secures on both edges (10 Qty)
Mounting Clip 2		<b>LED-TO24-C2</b>	Secures on one edge (10 Qty)
Mounting Clip 3		<b>LED-TO24-C3</b>	Spring clip secures beneath tape (10 Qty)
Joiner Cable		<b>LED-TO24-IC6</b>	6 in
		<b>LED-TO24-IC12</b>	12 in
		<b>LED-TO24-IC72</b>	72 in
		<b>LED-TO24-IC120</b>	120 in
4 Way "X" Connector		<b>LED-TO24-X</b>	Extends distance between transformers and controllers
3-Way "Y" Connector		<b>LED-TO24-Y</b>	
RGB Joiner Cable		<b>LED-TO24-IC6-RGB</b>	6 in
		<b>LED-TO24-IC12-RGB</b>	12 in
		<b>LED-TO24-IC72-RGB</b>	72 in
		<b>LED-TO24-IC120-RGB</b>	120 in
4 Way "X" Connector		<b>LED-TO24-X-RGB</b>	Extends distance between tape and controllers
3-Way "Y" Connector		<b>LED-TO24-Y-RGB</b>	

WAC LIGHTING  
Responsible Lighting®

wacighting.com  
1-800-526-2588